



30 Commerce Road
Rockland, MA 02370

Phone: 1-800-343-1076
Fax: 781-871-0065

Technical Data Sheet

Product No.:

2600 series

2608

2616

DOUBLE COATED FOAM MOUNTING TAPE

Description:

Venture's 2600 Series of double coated polyfoam tapes is constructed from white crosslinked polyethylene foam coated on both sides with the same extremely high tack synthetic adhesive system. This adhesive system exhibits excellent consistent quick stick even to low energy surfaces. This product also exhibits good resistance to humidity, mild acids, oil and grease. The foam has superior conformability and compressibility which allows it to adhere well to textured and irregular surfaces, and can easily be die cut.

Applications:

Mounting nameplates, signs, small die cast parts, mirrors, maps, etc. Used for sound and vibration dampening in business machines, industrial equipment, copy machines, electronic component packaging, glass panel mounts, seals, gaskets, etc.

TECHNICAL DATA

| | <u>Imperial</u> | <u>Metric</u> |
|---|------------------------|-----------------------|
| Adhesive thickness: | 4.0 mils (0.0040") | 0.1016 mm |
| Substrate Thickness: | 1/16", 1/8" | 1.6 mm, 3.18 mm |
| Peel Adhesion (PSTC-1): | 90 oz/inch | 25.7 N/2.5 cm |
| Shear Adhesion (PSTC-7): | Indefinite @ 2.2 psi | Indefinite @ 15.2 kPa |
| Maximum use Temperature: | 257°F | 125°C |
| Minimum application temperature: | 50°F | 10°C |
| Release Liner: | 4 mil | 100 micron |
| | | Blue HDPE |

The information listed is in good faith and has been established from sources believed to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.